

Gascoseeker 2-500



The gas industry standard instrument for measuring % LEL and % Volume flammable hydrocarbon gas.

- Automatic range selection
- Simple 2-button operation, allowing user access to all features
- Accurate and extremely reliable low-cost instrument
- Integral pump with flowpath protected by water filter
- Rugged carbon loaded polypropylene case, sealed to IP54 rating and suitable for outdoor use
- LCD with backlighting which displays the current gas readings (in both digital and analogue format) together with operational and status information
- Can be checked / calibrated, via an infrared link to GMI Auto Test Calibration Unit, without opening the instrument
- Comprehensive range of accessories
- ATEX approved






www.gmiuk.com

Detection, Protection, Innovation

GMI. CONFIDENCE WHERE SAFETY IS CRITICAL. Gas Measurement Instruments designs, manufactures and markets a wide range of the highest quality proven personal portable and fixed gas monitoring systems. GMI is an international brand with a worldwide network of distributors and dedicated service centres ensuring fast and effective turnaround on instrument calibration and repair. Our uncompromising engineering excellence, established in over half a century of leadership, enables us to meet the exacting demands of industries where safety is critical. By building and maintaining strong relationships with our customers, GMI understands the unique challenges of the diverse markets we serve. Today, our proud heritage of pioneering gas leak monitors and detectors is shaping the future of GMI.

Gascoseeker 2-500

TECHNICAL SPECIFICATIONS

Measuring Ranges:	0 to 100% LEL 0 to 100% VOL GAS
Resolution:	LEL 0 to 10% 0.1% 10 to 100% 1% VOL GAS 0 to 100% 1%
Physical Properties:	Weight: 1.7 kg (3.75lbs.) with alkaline batteries Dimensions: 180 x 95 x 105 mm. (7.08 x 3.74 x 4.13 in.)
Environment:	Temperature Limits: -20°C to + 50°C (-4°F to + 122°F) Humidity: 0 to 95% R.H. non-condensing
Construction:	Moulded polypropylene case protected to IP54
Display:	LCD containing: 4-digit digital display Analogue display 3-character range indication Operational flags
Sampling System:	Integral pump with flow fail sensor Sample path is protected by hydrophobic filter and automatic pump switch-off
Power Source:	Four 'D' size alkaline cells providing approx. 15 hours runtime at 20°C (68°F).
Expected Sensor Life:	Flammable 5 Years
Certification:	Ex iad IIC T4 Gb EEx iad IIc T4 (-20°C < Tamb < 50°C) BAS01ATEX2292  II 2 G  UL 913 Class I Groups A, B, C and D  CSA Class 1 Groups ABCD C22.2 No. 152



ORDERING INFORMATION AND ACCESSORIES

12212	GASCOSEEKER® 2-500 (Alkaline) Above instrument is supplied with: Field Carrying Case; Shoulder Harness; 4mm. Hex Driver; LR20 Batteries x 4; Plastic Probe 28cm. (11 in) Open End; Plastic Probe 80cm. (2ft 7in) Solid End; Aspirator Bulb; Probe Handle c/w Sample Line and Filters; Cotton Particulate Filters (Box of 10) x 2; User Handbook; Quick Operating Instruction Card.
42696	FlexiCal Calibration Software
13427	Plastic Probe - 35cm. Open End
12480	Plastic Probe - 35cm. Solid End
12393	Plastic Probe - 80cm. Solid End
12481	Probe Handle c/w Filters
10077	Cotton Particulate Filters (Box of 10)
13937	Charcoal Filters (Pack of 5)

For all other sampling probes and accessories, and for calibration gases, contact GMI Ltd



© 2008 Gas Measurement Instruments Ltd.



Gas Measurement Instruments Ltd

Gas Measurement Instruments Ltd.

Inchinnan Business Park
Renfrew
PA4 9RG
Scotland
Tel: +44 (0) 141 812 3211
Fax: +44 (0) 141 812 7820
sales@gmiuk.com
www.gmiuk.com

GMI Service and Calibration Division

25 Cochran Close
Crownhill
Milton Keynes
MK8 0AJ
Tel: +44 (0) 1908 568 867
Fax: +44 (0) 1908 261 056
service@gmiuk.com
www.gmiuk.com

Distributed by:

Gascoseeker 2-500 Series product brochure Part No. 99314
Issue 3 - 16/02/11

As an ISO 9001 approved company, Gas Measurement Instruments quality assurance programmes demand the continuous assessment and improvement of all GMI products. Information in this leaflet could thus change without notification and does not constitute a product specification. Please contact GMI or their representative if you require more details.